

-25°C Chest Biomedical Freezer



MD-25W568



Precise Temp. Control

Microcomputer Temperature Control System, temperature accuracy 0.1°C.



Super & Even Cooling

90mins Rapid Cooling(25°C→-25°C) & ≤3 Uniformity.




Eco-Cool Refrigerant

R290 (natural hydrocarbon, low-GWP) refrigerant ensures zero ozone depletion and lower climate impact .


LCD Temperature Control Systems



Three-dimensional seal




Cooling Speed(Ambient 25°C)




Safety Lock

Lockable door with key



USB Interface



Low Noise 58dB(A)



Multiple Alarms

Audible & Visual Alarms, High/Low Temperature Warnings, Power Failure Alert, Sensor Malfunction Monitoring



Backup Battery

Maintains alarms for 24 hours during power failure

Application, Rating, & Electrical Data

Application	Biomedical chest freezer
Storage Volume (L/Cu.Ft)	568/20.06
Temperature Range	-10°C~-25°C
Default Set Point	-25°C
Power	220~V/50Hz
Current	2A
Power Cord Length	1.7m
Certification	CE
Door type	Solid door
Application Environment	Non-corrosive, non-flammable, non-explosive
Ambient Operating Temperature	10°C-32°C

Refrigeration

Refrigeration System	Direct cooling
Compressor	Hermetic, fixed frequency
Condenser Type	Capillary tube
Expansion Device	Built in + micro channel condenser
Evaporator Type	Shelf evaporator
Defrost Method	Manual defrost
Refrigerant	R290

Controller / Configuration Settings

Display screen	LCD
Controller Type	Microprocessor
Security	Lockable door
Control Sensor	NTC
Communication Ports	USB
Power Failure Alarm	Yes
High/Low Alarms	Yes, fully adjustable
Door Ajar Alarm	Yes
Download	Yes, via USB
Temperature Log	Yes, download via USB

Performance Characteristics (normal operating conditions)

Uniformity (°C)	≤3°C
Energy consumption (kWh/day)	2.5
Noise emission (dB)	58
Pull-down time to -25°C (min)	90

Typical Temperature Map

Fre	test 1	test 2	test 3	test 4	test 5	test 6	test 7	test 8	test 9
Avg	-24.59	-24.89	-25.51	-26.29	-26.62	-25.87	-26.12	-26.65	-24.78
Max	-22.30	-22.52	-22.85	-23.63	-23.68	-23.43	-23.63	-24.11	-23.84
Min	-26.50	-26.69	-27.47	-27.94	-28.25	-27.61	-28.33	-28.50	-27.23

Midea Biomedical, Trademarks are the property of their respective owners. Drawings are not for engineering use, and specifications may change. Not all products are available in all countries, so please check with your local sales representative for details.
Midea Biomedical reserves right to interpret the data.




Dimensions and Construction

Interior (w*d*h)	1479*550*625 & 230*550*405 mm
Exterior (w*d*h)	1870*745*865 mm
Wheels	6 Swivel Casters + 2 Leveling Feet
Net Weight	75 kg
Gross Weight	88 kg

All performance data from 568L biomedical freezer, 25 ambient, -25°C

Uniformity



Cooling Speed

